



Technical Data

Environment, Health & Safety

- Biodegradable
- · Low Toxicity
- · No Phosphates
- · No Ozone Depleting Compounds
- No Known Carcinogens
- · No Chlorine Bleach
- · No Butoxyethanol
- · No Petroleum Distillates
- Low VOC Level
- · Recyclable Container

Specifications

SSS Item Numbers	48111
Available Sizes	2.5G
Color	White
Fragrance	
pH	8.5 – 9.0
Viscosity	Water thin
Foam	Low
Emulsification	Excellent
Biodegradability	Complete
Solubility	Complete with water
Flash Point	None
Storage/Stability	2 years
Weight Per Gallon	8.90 lbs./gal.
Freeze/Thaw Stability	Keep from freezing

HMIS Hazardous Materials I.D. System

Health	2
Flammability	1
Reactivity	0
Personal Protection	R

What the Pros Know

When stripping a floor, it is recommended to flood the floor using 1 gallon of diluted stripper for 100 square feet of flooring.

(1) Five gallon mop bucket of ready-to-use stripper should be used to strip 500 square feet of flooring.

Description


An environmentally friendly low-odor neutral pH stripper perfect for use in places where a high pH stripper cannot be used. Contains no ammonia, butyl, caustic or other harsh materials. This product is safe for the user and the environment, and contains no VOC levels that exceed established regulatory limits. Ideal for use on synthetic flooring such as rubber, linoleum or anywhere a high pH stripper will damage the substrate.

Directions

Wear safety equipment recommended on SDS, place Wet Floor Signs and read all directions and cautions prior to beginning your work.







- 2. Dilute 1:2 to 1:6 with cold water depending on age and build-up of finish.
- 3. Apply liberally to synthetic floor with a mop. Allow floor to stand wet for 5-10 minutes. Do not allow floor to dry, and re-wet if necessary
- 4. Agitate synthetic floor with a low speed floor machine equipped with a soft nylon brush. You can also agitate manually with a deck brush.
- 5. Rinse thoroughly with clear water to remove residue as necessary.

NOTE: Do not use this product on wood floors or painted surfaces.



Low Odor

Contains No Ammonia, No Butyl

Safe for User and Environment



PRODUCT CERTIFIED FOR REDUCED ENVIRONMENTA IMPACT. VIEW SPECIFIC ATTRIBUTES EVALUATED: UL.COM/EL UL 2777



