



TAKE DOWN

LOW ODOR FLOOR STRIPPER

REMOVEDOR DE CERA DE PISO

Technical Data

Areas of Use

A concentrated emulsifying stripper. Tough, fast acting, non-butyl formula for removal of UHS and conventional resilient floor coatings.

- Hospitals, nursing homes, doctors offices
- Schools, universities, child care centers
- Malls, retail stores, supermarkets

Specifications

SSS Item Numbers:.....48054, 48055, 48142
 Available Sizes:.....1G, 5G, & 55G
 Physical State:.....Liquid
 Color:.....Colorless
 Fragrance:.....Low Odor
 Ammoniated:.....No
 Viscosity:.....Water thin
 Foam:.....Low
 Water Based:.....Yes
 Emulsifier:.....Extra Heavy Duty
 Flash Point:.....Nonflammable
 Specific Gravity:.....1.028
 pH:.....10.5-11.0
 Storage/Stability:.....1 Year

HMIS Hazardous Materials I.D. System

Health.....2
 Flammability.....0
 Reactivity.....0
 Personal Protection.....B

- Removes new zinc-free floor finishes as well as conventional floor finishes.
- Dissolves multiple coats of finish without harsh alkalis, butyl cellosolve, or strong ammonia odors.
- Rinse-free characteristics leave no residue left behind to interfere with subsequent finish applications.

Take Down is a very low odor, non-toxic, non-corrosive, non-butyl floor seal and finish remover. Specially designed to remove metal-free floor finishes as well as conventional floor finishes. This fast-acting stripper dissolves multiple coats of finish without harsh alkalis, butyl cellosolve, or strong ammonia odors. No neutralizing needed. Controlled foam and free-rinsing characteristics assure that no residue is left behind to interfere with subsequent finish applications.

Directions

Wear safety equipment recommended on MSDS, place Wet Floor Signs and read all directions and cautions prior to beginning your work.



1:4 - 1:8



Machine Stripping - Heavy Build Up: Dilute 1:4 (32 ounces per gallon of water) Light to Medium Build Up: Dilute 1:8 (16 ounces per gallon of water) NOTE: USE WITH COLD WATER ONLY

DIRECTIONS: Apply a test solution in an out of the way area to ensure that the floor tile will not "color bleed" or otherwise be affected by the stripping solution. If there is no adverse affect:

1. Apply the stripping solution at the rate of 150 to 300 square feet per diluted gallon. Apply liberally enough to ensure complete wetting of the floor.
2. Allow TAKE DOWN to work for 5 to 10 minutes. Do not allow the floor to dry. Apply more solution if needed.
3. If machine stripping scrub the floor with a Triple S PT 2000 High Performance Stripping Pad or equivalent.
4. Pick up the solution with a wet vacuum, auto scrubber or mop and bucket. Change water often when using a mop & bucket for pick up.
5. Damp mop the floor with clean cool water to remove all remaining residue. Change rinse water frequently.
6. Allow the floor to dry thoroughly before applying seal or finish.



Low Odor

Fast Acting

No Rinse



ECOLOGO

PRODUCT CERTIFIED FOR REDUCED ENVIRONMENTAL IMPACT. VIEW SPECIFIC ATTRIBUTES EVALUATED: UL.COM/EL UL 2777

