SAFETY DATA SHEET

Bona®

Bona SuperCourt Poly 350

Section 1. Identit	fication
GHS product identifier	: Bona SuperCourt Poly 350
Product code	: Not available.
Other means of identification	:
Product type	: Liquid.
	f the substance or mixture and uses advised against
Not applicable.	
Supplier's details	: BonaKemi USA, Inc. (dba Bona US) 24 Inverness Place E. Suite #100 Englewood, CO 80112 (303) 371-1411
Emergency telephone number (with hours of operation)	: 24 Hour Emergency Number: call CHEMTREC: US - 1-800-424-9300, International - 1-703-527-3887
Section 2. Hazar	ds identification
OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	 FLAMMABLE LIQUIDS - Category 3 SKIN CORROSION/IRRITATION - Category 2 TOXIC TO REPRODUCTION (Fertility) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
GHS label elements	
Hazard pictograms	
Signal word	
Hazard statements	 Flammable liquid and vapor. Causes skin irritation. Suspected of damaging fertility. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure.
Precautionary statements	-
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Section 2. Hazards identification

Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non- sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.
Response	: Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. If skin irritation occurs: Get medical attention.
Storage	: Store in a well-ventilated place. Keep cool.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Other means of identification	:	
Identification		

Ingredient name	%	CAS number
Stoddard solvent	≥25 - <50	8052-41-3
octamethylcyclotetrasiloxane	≥25 - <50	556-67-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Section 4. First aid measures

In	~ ~	•	0	-

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects	
Eye contact	: No known significant effects or critical hazards.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: Causes skin irritation.
Ingestion	: Can cause central nervous system (CNS) depression.
Over-exposure signs/sympto	<u>ms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate medic	al attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Date of issue/Date of revision	: 2020-05-08	Date of previous issue	: 2018-12-18	Version : 1.01	3/14
	. 2020 00 00	Bate of providuo locad			0, 1 1

Section 5. Fire-fighting measures

-	_
Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
ntainment and cleaning up
: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters Occupational exposure lin	<u>nits</u>					
None.						
Appropriate engineering controls	other eng recomme vapor or	with adequate ventilation. gineering controls to keep vended or statutory limits. T dust concentrations below n equipment.	worker exposure to air he engineering contro	borne contaminants be bls also need to keep ga	elow any as,	
Environmental exposure controls	they com cases, fu	s from ventilation or work p ply with the requirements of me scrubbers, filters or en ecessary to reduce emissio	of environmental prote gineering modification	ection legislation. In some to the process equipment	me	
Individual protection meas	<u>ures</u>					
Hygiene measures	eating, s Appropri Wash co	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.				
Eye/face protection	assessm gases or	vewear complying with an a ent indicates this is necess dusts. If contact is possib ssment indicates a higher o	sary to avoid exposure le, the following protect	e to liquid splashes, mis ction should be worn, u	sts, nless	
Date of issue/Date of revision	: 2020-05-08	Date of previous issue	: 2018-12-18	Version : 1.01	5/14	

Section 8. Exposure controls/personal protection

Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	1	Liquid.
Color	:	Amber.
Odor	:	Mineral Spirits
Odor threshold	:	Not available.
рН	:	Not applicable.
Melting point	:	Not available.
Boiling point	:	161 to 198°C (321.8 to 388.4°F)
Flash point	:	Closed cup: 46°C (114.8°F) [Setaflash.]
Evaporation rate	1	Not available.
Flammability (solid, gas)	1	Not available.
Lower and upper explosive (flammable) limits	:	Lower: 0.75% Upper: 7.4%
Vapor pressure		
vapor pressure		
Vapor density	÷	Not available.
		Not available. 0.91
Vapor density	:	
Vapor density Relative density	1	0.91
Vapor density Relative density Solubility		0.91 Insoluble in the following materials: cold water and hot water.
Vapor density Relative density Solubility Solubility in water Partition coefficient: n-	:::::::::::::::::::::::::::::::::::::::	0.91Insoluble in the following materials: cold water and hot water.0 g/l
Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water		0.91 Insoluble in the following materials: cold water and hot water. 0 g/l Not available.
Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water Auto-ignition temperature		0.91 Insoluble in the following materials: cold water and hot water. 0 g/l Not available. 260 to 400°C (500 to 752°F)
Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water Auto-ignition temperature Decomposition temperature		0.91 Insoluble in the following materials: cold water and hot water. 0 g/l Not available. 260 to 400°C (500 to 752°F) Not available.
Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water Auto-ignition temperature Decomposition temperature Viscosity		0.91 Insoluble in the following materials: cold water and hot water. 0 g/l Not available. 260 to 400°C (500 to 752°F) Not available.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
octamethylcyclotetrasiloxane	LC50 Inhalation Vapor LD50 Dermal LD50 Oral	Rat	36 g/m³ 1770 mg/kg 1540 mg/kg	4 hours - -

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Stoddard solvent	Eyes - Mild irritant	Human	-	100 parts per million	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
octamethylcyclotetrasiloxane	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Section 11. Toxicological information

Stoddard solvent Specific target organ toxi				exposure		
Specific target organ toxi		Category	3	Not applicable.	Narcotic effects	
	city (repeated exposure	<u>)</u>		•	•	
Name		Categor	y	Route of exposure	Target organs	
Stoddard solvent		Category	1	Inhalation	central nervous system (CNS)	
Aspiration hazard						
Name			Res	ult		
Stoddard solvent			ASP	IRATION HAZARI	D - Category 1	
nformation on the likely outes of exposure	: Not available.					
Potential acute health effect	<u>cts</u>					
Eye contact	: No known significa					
Inhalation	dizziness.	nervous system (C	NS) depi	ession. May caus	e drowsiness or	
Skin contact	: Causes skin irritati					
Ingestion	: Can cause central	nervous system (C	NS) depi	ession.		
Symptoms related to the p				<u>s</u>		
Eye contact	: Adverse symptoms pain or irritation watering redness	s may include the fo	ollowing:			
Inhalation	: Adverse symptoms nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weig increase in fetal de skeletal malformat	ht eaths	llowing:			
Skin contact	: Adverse symptoms irritation redness reduced fetal weig increase in fetal de skeletal malformat	ht	llowing:			
Ingestion	: Adverse symptoms reduced fetal weig increase in fetal de skeletal malformat	ht eaths	llowing:			
<u>Delayed and immediate eff</u> Short term exposure	ects and also chronic e	ffects from short a	and long	<u>ı term exposure</u>		
Potential immediate effects	: Not available.					
Date of issue/Date of revision	: 2020-05-08 Date of	of previous issue	: 2018-1	12-18	ersion : 1.01	

Section 11. Toxicological information

	-
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
General	: Causes damage to organs through prolonged or repeated exposure.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
	Chronic NOEC 1.7 to 15 µg/l Fresh water Chronic NOEC 4.4 µg/l Fresh water		21 days 93 days

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
octamethylcyclotetrasiloxane	6.488	13400	high

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ADR/RID	IMDG	ΙΑΤΑ
UN number	UN1263	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)		3	3			3
Packing group	111	Ш	ш	ш	Ш	Ш
Environmental hazards	Yes.	No.	No.	Yes.	Yes.	No.
Additional information	This product may be re- classified as "Combustible Liquid," unless transported by vessel or aircraft. Non- bulk packages (less than or equal to 119 gal) of combustible liquids, that are marine pollutants, are not regulated as hazardous materials, unless			The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. <u>Special</u> <u>provisions</u> 640 (E) <u>Tunnel code</u> (D/E)	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.	The environmentall hazardous substance mark may appear if required by other transportation regulations.

Bona SuperCo	Bona SuperCourt Poly 350						
Sectio	n 14. Transport i	nformatio	ו				
	transported by vessel.						
	The marine pollutant mark is not required when transported on inland waterways in sizes of ≤5 L or ≤5 kg or by road, rail, or inland air in non-bulk sizes.						

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to Annex II of MARPOL and the IBC Code

Section 15. Regulatory information

•		•	
U.S. Federal regulations	:	TSCA 4(a) final test rules: nonane	
		TSCA 8(a) PAIR: octamethylcyclotetrasiloxane; nonane	
		TSCA 8(a) CDR Exempt/Partial exemption: Not determined	
		Clean Water Act (CWA) 307: ethylbenzene	
		Clean Water Act (CWA) 311: ethylbenzene	
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	:	Not listed	
Clean Air Act Section 602 Class I Substances	:	Not listed	
Clean Air Act Section 602 Class II Substances	:	Not listed	
DEA List I Chemicals (Precursor Chemicals)	:	Not listed	
DEA List II Chemicals (Essential Chemicals)	:	Not listed	
SARA 302/304			
Composition/information	on	ingredients	
No products were found.			
SARA 304 RQ	:	Not applicable.	
SARA 311/312			
Classification	:	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
Deter firmer (Deter structure)			

Section 15. Regulatory information

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Stoddard solvent octamethylcyclotetrasiloxane	≥25 - <50	Yes.	No.	No.	Yes.	Yes.
	≥25 - <50	Yes.	No.	No.	No.	Yes.

State regulations

Massachusetts	: The following components are listed: STODDARD SOLVENT
New York	: None of the components are listed.
New Jersey	: The following components are listed: STODDARD SOLVENT
Pennsylvania	: The following components are listed: STODDARD SOLVENT

California Prop. 65

WARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer.

Ingredient name	Cancer	•	_	Maximum acceptable dosage level
ethylbenzene	Yes.		41 μg/day (ingestion) 54 μg/day (inhalation)	No.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

International lists

Date of issue/Date of revision	: 2020-05-08	Date of previous issue	: 2018-12-18		
Turkey	:				
Taiwan	: Not deterr	nined.			
Republic of Korea	: Not determined.				
Philippines	: Not determined.				
New Zealand	: Not determined.				
Malaysia	: Not determined.				
Japan	: Not deterr	nined.			
Europe	: Not determined.				
China	: Not determined.				
Canada	: All components are listed or exempted.				
Australia	: Not deterr	nined.			
National inventory					

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

	Classif	ication		Justification		
FLAMMABLE LIQUIDS - Category 3 SKIN CORROSION/IRRITATION - Category 2 TOXIC TO REPRODUCTION (Fertility) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1				On basis of test data Calculation method Calculation method Calculation method Calculation method		
History						
Date of printing	: 2021-08-1	0				
Date of issue/Date of revision	: 2020-05-0	8				
Date of previous issue	: 2018-12-1	8				
Version	: 1.01					
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)					
Date of issue/Date of revision	: 2020-05-08	Date of previous issue	: 2018-12-18	Version : 1.01 13/14		

Section 16. Other information

UN = United Nations

References

: Not available.

✓ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.