

PRO SERIES

NANOFORCE

NANO POWERED FLOOR FINISH

NANO ACABADO DE PISOS POWERED



Technical Data

Areas of Use

- Classrooms
- Healthcare facilities
- Office buildings
- Hallways
- Entrances
- Hospitals
- Vinyl Tiles
- Linoleum
- Terrazzo
- Quarry Tile
- Slate
- Concrete

Specifications

SSS Item Numbers ..48156,48157,48158,48159
 Available Sizes.....1G, 2.5G, 5G, 55G
 Physical State.....Liquid
 ColorMilky emulsion
 FragranceMild
 pH8.0 -9.0
 Non-Volatile Solids.....22%
 Dry/Recoat time.....30 minutes min.
 Coverage2000-2500 sq. ft./gal.
 Detergent Resistance.....Excellent
 Gloss.....Good-Excellent
 Leveling.....Excellent
 Buffability.....Spray Buff or Restorer
 Removability.....With instant type strippers
 Type.....Nano Infused Pure Acrylic
 Storage/Stability2 years
 Weight Per Gallon8.51 lbs./gal.
 Freeze/Thaw StabilityKeep from freezing

HMIS Hazardous Materials I.D. System

Health1
 Flammability0
 Reactivity0
 Personal ProtectionA

What the Pros Know

Nanoforce is infused with a Nano-additive. This nano-additive provides exceptional durability, scratch & dirt resistance, and advanced leveling properties - an easy decision for any scrub and recoat program.

Description

A pure acrylic finish formulated with a nano-additive that provides outstanding scratch resistance, abrasion resistance, and durability. The nano-additive significantly improves leveling properties which allows the finish to be distributed uniformly; ultimately easing the application process. For its ultra-durable and low maintenance properties, it is the cost conscious choice for high traffic areas. This 22% solids styrene-free floor finish is well suited for scrub and recoat programs. Daily dust mopping and damp mopping, spray buffing, and mop on restorers keep your floors looking beautiful, even after multiple recoats. This finish will not yellow and can be stripped easily with conventional floor strippers.

Directions

Wear safety equipment recommended on MSDS, place Wet Floor Signs and read all directions and cautions prior to beginning your work.



PREPARATION: If stripping is necessary, use a high quality stripper and follow the directions accordingly. Follow with a thorough rinsing and allow floor to dry completely. If stripping is not necessary; sweep up loose dirt and dust. Clean with a quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow floor to dry completely.



FINISHING: Spread a liberal coat of finish evenly across the floor with a clean mop or applicator. Allow each coat to dry at least 30 minutes before applying the next coat. Four to five coats is ideal initially, depending on the condition of the floor and desired gloss.



MAINTENANCE: The floor may be maintained using a quality floor cleaner and damp mopping regularly. Spray buffing or mop-on restoring may also be done after sweeping up loose dirt and dust. Follow directions for each product accordingly. This product meets the maximum content requirements for Volatile Organic Compounds (VOCs) as established by state and Federal regulations.

Formulated with a Nano-additive

Contains No Styrene

Low Maintenance

