

PRO SERIES

RED ZONE

**HIGH POWERED
LOW ODOR FLOOR STRIPPER**
SEPARADOR DEL PISO



Technical Data

Areas of Use

- Vinyl Tile
- Terrazzo
- Ceramic Tile
- Flagstone

Specifications

SSS Item Number	48110
Available Sizes	1Qt
Color	Light Amber
Fragrance	Mild odor
pH	11.5 - 12.5
Viscosity	Water thin
Foam	Low
Phosphate Content	None
Solubility	Complete with water
Flash Point	153°F (TCC)
Storage/Stability	2 years
Weight Per Gallon	8.45 lbs./gal.
Freeze/Thaw Stability	Keep from freezing

HMIS Hazardous Materials I.D. System

Health	3
Flammability	2
Reactivity	0
Personal Protection	D

What the Pros Know

When stripping a floor, it is recommended to flood the floor using 1 gallon of diluted stripper for 100 square feet of flooring.

Description

An ultra concentrated (1:20) high-powered stripper that rapidly penetrates and strips off floor finish. A powerful solvent combined with amines, penetrates and removes multiple coats of burnished finish with minimum labor. Low odor formula is ideal for use in areas where odors are a concern. This high productivity floor stripper strips floor finishes completely on the one pass and requires no rinse. This unique formula provides the lowest end-use cost per gallon due to its ultra concentration.

DO NOT USE THIS PRODUCT ON WOOD FLOORS OR PAINTED SUFRACES.

Directions

Wear safety equipment recommended on SDS, place Wet Floor Signs and read all directions and cautions prior to beginning your work.



FOR STRIPPING: Add 1 quart of concentrate per 5 gallons of warm water.

1. After sweeping the floor clean, apply at a rate of 150-300 square feet per gallon. Apply liberally to ensure complete wetting. Be sure to completely cover floor to baseboards.
2. Allow to stand for 5 to 10 minutes, **DO NOT ALLOW TO DRY.**
3. Scrub the wet floor with a floor machine using a stripping pad to break the softened film scrub.
4. Pick up solution using a mop, wet vac or automatic scrubber. If mop is used for pick-up, use extreme care to remove all residue and change water frequently.
5. **RINSE THOROUGHLY** with clean, cool water to remove all residues and allow to dry before applying finish.

NOTE:

The product must be used only as directed due to its unique penetrating and liquefying ability. Do not use undiluted product. Do not dilute with hot water. To determine the optimum use-dilution, pretest on a small area. Wet floor may become extremely slippery. Be sure to keep pedestrian traffic away from floor until thoroughly dry. Work area should have adequate ventilation since prolonged exposure to high concentrations of vapors may be harmful to eyes, skin and respiratory tracts. As prolonged soaking in concentrated strippers may damage some asphalt tiles, a spot test is recommended before general use.

*Ultra
Concentrated-
One Quart Makes
5 Gallons*

Low Odor

*Low End Use
Cost*

