



Ultron 20TO

Orbital Automatic Scrubber



Better Cleaning. Better Performance. Better Results.

Ultron 20TO

Orbital Automatic Scrubber



Deep orbital cleaning action



Easy to understand controls

Self-propelled, traction drive, orbital automatic scrubber for today's cleaning professional. Scrubs deeper and more uniformly leaving your floors ready and prepped for finishing. Large tank means less refills reducing your labor. Robust machine constructed of parts made of die-cast aluminum and steel provide for durability and toughness. For today's environmentally-conscious facilities – requires less water and chemicals for scrubbing and removing floor finish.

Benefits:

- Orbital scrubbing technology scrubs deeper and more uniformly.
- Oversized 15-gallon solution tank improves working efficiency.
- Touch panel control system is state-of-the-art and user-friendly.
- Durable die-cast aluminum brush deck and squeegee assembly.
- No tools needed for changing curved squeegee blades.
- Variable 65 lb or 100 lb pad pressure.
- Delayed vacuum motor shutoff eliminates pooling.
- Emergency shutdown system for safety.
- Includes on-board charger and squeegee assembly.
- 5 YEAR WARRANTY on all parts and labor with the exception of "wearables" such as brushes, pad drivers, batteries, hoses, belts, and switches. Lifetime parts warranty/ three years labor on orbital isolators.

Where to use:

- Schools and universities.
- Healthcare – acute and long term care.
- Office, commercial and industrial spaces.
- Retail stores, shopping malls, grocery stores.
- Government facilities.

Specifications

Model	Ultron 20TO
Item #	17023
Productivity rate	23,680 ft ² / hr
Drive system	Transaxle, 0.27hp / 0.2KW
Travel speed, maximum	246 ft / min
Weight	230 lbs
Weight with batteries	440 lbs
Recovery tank capacity	17.2 gal
Solution tank capacity	15.9 gal
Squeegee width	30 in
Cleaning path width	20 in (20 in x 14 in Pad)
Brush speed	2200 RPM / min
Wheel diameter	8 in
Minimum aisle turn	63 in
Pad / brush pressure	65 lbs / 100 lbs Max
Solution flow rate	0 ~ 0.37 gal / min
Brush motor	0.75 hp / 0.55 KW 2,200 RPM
Vacuum motor	0.7 hp / 0.5 KW
Vacuum water lift	45 in H ₂ O
Batteries	Requires 2-12V (Available in Wet & AGM)
Run time per charge	3 Hours
Voltage DC	24 V
Decibel rate at operator's Ear, indoors	<70 dB(A)
Grade level, max	5% (3°)
Dimensions L x W x H	55.7 x 22 x 44.9 in

Specifications are subject to change without notice.